



FDE112KXZE1

11.2kW

Specifications

Nominal cooling capacity		kW	11.2
Nominal heating capacity		kW	12.5
Power source			1 Phase 220-240V, 50Hz
Power consumption	Cooling	kW	0.10-0.10
	Heating	kW	0.10-0.10
Sound pressure level Cooling		db(A)	P-Hi:45 Hi:42 Me:38 Lo:34
Exterior dimensions unit	H x W x D	mm	250 x 1620 x 690
Net weight		kg	43
Air flow		m ³ /min	P-Hi:28 Hi:25 Me:21 Lo:16.5
Outside air intake			Not possible
Air filter, Q'ty			Pocket Plastic net x2 (Washable)
Remote control(option)			wired:RC-EX3A, RC-E5, RCH-E3 wireless:RCN-E-E3
Installation data Refrigerant piping size		mm(in)	Liquid line:ø9.52(3/8") Gas line:ø15.88(5/8")

The data are measured under the following conditions(ISO-T1).

Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB.

Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

External static pressure of indoor unit is 10Pa.

The sound level indicates the value of rear-intake type with duct in anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

Schematics

≡1, 140KXZE1

