



FDFW45KXE6F

4.5kW

Specifications

Nominal cooling capacity		kW	4.5
Nominal heating capacity		kW	5.0
Power source			1 Phase 220-240V, 50Hz
Power consumption	Cooling	kW	0.02-0.02
	Heating	kW	0.02-0.02
Sound power level		dB(A)	57
Sound pressure level Cooling		dB(A)	Hi:38 Me:36 Lo:33
Exterior dimensions unit	H x W x D	mm	600x860x238
Net weight		kg	20
Air flow		m ³ /min	Hi:9 Me:8 Lo:7
Air filter, Q'ty			Polypropylene net x1 (Washable)
Remote control(option)			wired:RC-EX3A, RC-E5, RCH-E3 wireless:RCN-FW-E2
Installation data Refrigerant piping size		mm(in)	Liquid line:ø6.35(1/4") Gas line:ø12.7(1/2")

The data are measured under the following conditions(ISO-T1).

Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB.

Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

External static pressure of indoor unit is 10Pa.

The sound level indicates the value of rear-intake type with duct in anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

Schematics

