



## FDUM160KXE6F

### Specifications

Nominal cooling capacity		kW	16.0
Nominal heating capacity		kW	18.0
Power source			1 Phase 220-240V, 50Hz
Power consumption	Cooling	kW	0.45-0.45
	Heating	kW	0.45-0.45
Sound pressure level Cooling		db(A)	P-Hi:47 Hi:40 Me:35 Lo:30
Exterior dimensions unit	H x W x D	mm	280 x 1370 x 740
Net weight		kg	54
Air flow		m <sup>3</sup> /min	P-Hi:48 Hi:35 Me:28 Lo:22
Maximum external static pressure		Pa	100
Outside air intake			Possible
Air filter, Q'ty			Filter kit:UM-FL1EF/UM-FL2EF/UM-FL3EF(option)
Remote control(option)			wired:RC-EX3A, RC-E5, RCH-E3 wireless:RCN-KIT4-E2
Installation data Refrigerant piping size		mm(in)	Liquid line:ø9.52(3/8") Gas line:ø15.88(5/8")

The data are measured under the following conditions(ISO-T1).

Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB.

Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

External static pressure of indoor unit is 10Pa.

The sound level indicates the value of rear-intake type with duct in anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

## Schematics

### 140KXE6F, 160KXE6F

