



## FDUM71KXE6F

### Specifications

Nominal cooling capacity		kW	7.1
Nominal heating capacity		kW	8.0
Power source			1 Phase 220-240V, 50Hz
Power consumption	Cooling	kW	0.20-0.20
	Heating	kW	0.20-0.20
Sound power level		dB(A)	65
Sound pressure level Cooling		db(A)	P-Hi:38 Hi:33 Me:29 Lo:25
Exterior dimensions unit	H x W x D	mm	280 x 950 x 635
Net weight		kg	34
Air flow		m <sup>3</sup> /min	P-Hi:24 Hi:19 Me:15 Lo:10
Maximum external static pressure		Pa	100
Outside air intake			Possible
Air filter, Q'ty			Filter kit:UM-FL1EF/UM-FL2EF/UM-FL3EF(option)
Remote control(option)			wired:RC-EX3A, RC-E5, RCH-E3 wireless:RCN-KIT4-E2
Installation data Refrigerant piping size		mm(in)	Liquid line:ø9.52(3/8") Gas line:ø15.88(5/8")

The data are measured under the following conditions(ISO-T1).

Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB.

Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

External static pressure of indoor unit is 10Pa.

The sound level indicates the value of rear-intake type with duct in anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

## Schematics

### KXE6F

